

## ADLER Allwetterlack

## 50020 ff

Product description	Colourless synthetic resin varnish for use on wood in exterior and interior applications. Marine quality.
Specific properties	Low odour, quick drying; very good resistance to cream and grease. <b>Please note: has yellowish shade</b>
Fields of application	Interior and exterior use on wood, such as garden furniture, beer tables and doors. Also for varnishing of synthetic resin varnishes and water-thinnable coloured paints in order to avoid abrasion of colour.
Application	Brush, roller, spray Spraying is only allowed in spraying booths complying with the VOC directive.
Surface preparation	Wood: sand with grit 120. First impregnate exterior wood surfaces with Pullex Imprägnier-Grund 50208 ff. Before overcoating sand fully dried paint with grit 220.
Topcoat	Apply 2 coats of ADLER Allwetterlack 50020 ff.
Thinning	ADLER Allwetterlack 50020 ff can be applied by brush without thinning. Add up to 5% ADLER Adlerol 80301 for roller application and thin with 20% ADLER KH-Spritzverdünnung 80367 for spray application.
Application and object temperature	Above + 5 °C
Drying time (room temperature 20 °C)	Dust dryafter ca. 2 hoursTack freeafter 4 hoursCan be overpaintedafter ca. 12 hoursDrying times are longer for thick coatings and/or lowtemperatures and/or high humidity.
Tools	Clean with ADLER Adlerol 80301.
Coverage (per coat)	Ca. 10 m <sup>2</sup> /l and per coat
11-09 (replaces 01-07)	ADLER-Werk Lackfabrik, A-6130 Schwaz

ADLER-Werk Lackfabrik, A-6130 Schwaz Fon: 0043/5242/6922-190, Fax: 0043/5242/6922-309, Mail: <u>info@adler-lacke.com</u>

Our instructions are based on the current knowledge and are intended to advise the buyer/user to the best of our knowledge. They must be, however, individually adapted to the application areas and conditions. The buyer/user takes responsibility for the suitability and use of the delivered product. It is therefore recommended to produce a sample specimen for testing the suitability of the product. Otherwise our General Terms of Sale apply. All previous specifications become invalid with this edition. Packaging sizes, colors and available gloss values are subject to change.

Packaging 375 ml, 750 ml, 5 l, 25 l

Colours Colourless gloss 50020 Colourless matt 50023

**Special instructions** Colourless coatings on exterior surfaces require more frequent maintenance and care. Any damage should be repaired as quickly as possible to prevent discolouration.

Safety information Please consult Safety Data Sheet!

There is a risk that cloths may self-ignite when impregnated with substances creating oxidative reactions when dry! Impregnated cloths should be spread out for drying and stored in closed metal containers or in water.

The product must not be used in spray booths contaminated with nitrocellulose spray residues, due to the risk of self-ignition!