

## ADLER Beton-Siegel

42700 ff

<b>Product Description</b>	Water-thinnable, single-component sealant for indoor use.
<b>Special Properties</b>	<b>Resistant to heating oil as per DIN 53168</b>
<b>Areas of application</b>	<b>Cellar floors, stairs and heating oil trays</b> <b>Water-thinnable ADLER 2K-Epoxi-Beschichtung is recommended for garages and industrial flooring!</b>
<b>Application method</b>	Smearing (acrylic brush) Roller (short-bristle roller brush)
<b>Preparation of the substrate</b>	Remove greasy or oily impurities thoroughly and roughen up or grind particularly smooth screeds (sintered layers) in order to achieve sufficient adhesion and bonding. Apply water-thinnable ADLER Tiefengrund before the first coat on sanded substrates. Drying time: approx. 5 hours
<b>Primer coat</b>	1 x with ADLER Beton-Siegel, with max. 10 % dilution
<b>Top coat</b>	1 x with ADLER Beton-Siegel, without dilution
<b>Dilution (thinning)</b>	Water
<b>Processing and object temperature</b>	Not below + 10 °C High atmospheric humidity and / or low temperatures delay the drying process.
<b>Drying time</b>	Can be recoated after approx. 3 hours Can be treaded on after approx. 5 hours
<b>Tools and Equipment</b>	Clean them with water immediately after use. Remove dried-up paint residues with ADLER Abbeizer.
<b>Yield</b>	6 – 8 m <sup>2</sup> /l per coat
<b>Packaging</b>	750 ml; 2.5 l and 10 l
<b>Storage</b>	Store it in a cool place that is frost-free
<b>Storage stability</b>	3 years in the original sealed containers
<b>Colour shades</b>	Kieselgrau (Pebble grey) 42700 (Basic shade) Graubeige (greyish beige) 42701 Betongrau (Concrete-grey) 42706
<b>Safety-relevant information</b>	Please take note of and follow the safety data sheet! The customary safety precautions must be observed and followed even when processing low-pollutant products.

09-13 (supersedes 03-92)

ADLER-Werk Lackfabrik, A-6130 Schwaz

Fon: 0043/5242/6922-301, Fax: 0043/5242/6922-309, Mail: [technical-support@adler-lacke.com](mailto:technical-support@adler-lacke.com)

Our instructions for use are based on knowledge available currently and shall guide the purchaser / user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The purchaser / user decides about the acceptance and use of the delivered product at his / her own risk, which is why we recommend that a sample piece be prepared to check the acceptability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for modification of the container sizes, colour shades and degree of gloss.