

ADLER Pigmofix M

90698

Solvent-based matt paste for pigmented ADLER 2K-PUR furniture varnishes for industrial and professional use

	PRODUCT DESCRIPTION
General	Solvent-based matt paste for reducing the gloss level in pigmented 2-component PUR furniture lacquers. Excellent scratch resistance, uniform matting of the entire system.

Application areas





 Solvent-based pigmented varnishes for furniture and interior fnishing.

PROCESSING

Instructions for use



- Please stir the product before use.
- ADLER Pigmofix M 90698 must be carefully stirred into the unhardened and undiluted paint; then incorporate hardener and the required dilution quantity.
- Mixed varnishes must be processed as specified in the corresponding technical data sheet.

Quantity to be added



max. 15 per cent by weight to paint.

Example: Gloss reduction in Aduro MDF-4in1 G50 2205

For: Aduro MDF-4in1 G50	Degree of gloss achieved (85 ° angle)
0 %	G50
7 %	approx. G30
15 %	approx. G10

Drying times

(at 23 °C and 50 % rel. humidity)

The drying of the coating systems is not influenced by adding ADLER Pigmofix M 90698.

Cleaning the working equipment



With ADLER DD-Verdünnung 80019 or ADLER Waschverdünnung 80077.

05-17 (supersedes 10-16) ZKL 8106

ADLER-Werk Lackfabrik (Paints factory), A-6130 Schwaz

Tel: 0043/5242/6922-190, Fax: 0043/5242/6922-309, Mail: technical-support@adler-lacke.com

Our instructions for use are based on knowledge available currently and shall guide the purchaser / user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The buyer/user takes responsibility for the suitability and use of the delivered product. It is therefore recommended to produce a sample specimen for testing the suitability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for the modification of the container sizes, colour shades and degrees of gloss available.

	ORDERING INFORMATION
Size of trading unit	600 g; 3 kg
	FURTHER DETAILS
Durability/storage	At least 1 year in the original sealed containers. Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).
Safety-related information	Please pay attention to the associated safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com . The product is only suitable for industrial and professional use.