

ADLER Silberlack (*silver paint*)

54814



10 % 80367

Product description

Weather-proof, thixotrope, metallic satin-finished special-effect paint on alkyd resin basis with rust protection, heat-resistant up to approx. 150°C.

Fields of application

On metal and wood for indoor and outdoor application.

Application

Coating, rolling, spraying

Spraying is only permitted in spray booths subject to the VOC Directive.

Surface pre-treatment

The surface must be non-crackling, clean and grease-free.

Old coats

Remove loose coats. Slightly sand bonded coats and verify whether they are compatible with ADLER Silberlack (*silver paint*). If necessary, strip the entire old coat.

Metal

Steel: The metal parts must be clean, grease-free and dry.
Zinc, aluminium: For adhesiveness, apply ADLER Unigrund and/or ADLER 2K Exproxi-Grund (*2-component epoxy primer*)

Wood

For exterior surfaces, first apply Pullex-Imprägniergrund (*impregnation primer*)

Topcoat

ADLER Silberlack (*silver paint*) 2x

Thinner

Do not thin if you use brushes or rollers.
For spraying, thin with approx. 10 % ADLER KH-Spritzverdünnung (*synthetic spray thinner*).

Application and object temperature

At least + 5 °C

Drying time

(room temperature 20°C)
(100 µm wet coat)

Completely dry 2 hours
Repaintable after 8 - 10 hours

Strong coat thickness, low temperatures and/or high humidity may result in a significantly longer drying time.

Working equipment

Clean with ADLER KH-Spritzverdünnung (*synthetic spray thinner*).

Spreading rate

Approx. 10 m²/l

03-07 (replaces 02-07)

ADLER-Werk Lackfabrik, A-6130 Schwaz, 05242/6922-450

Our instructions are based on current knowledge and are intended to advise the buyer/user to the best of our knowledge. However, they must be individually adapted to the application areas and processing conditions. The buyer/user takes responsibility for the suitability and use of the delivered product. It is therefore recommended to produce a sample specimen in order to test the suitability of the product. Otherwise our General Terms of Sale apply. All previous specifications become invalid with this edition. Packaging sizes, colours and available gloss values are subject to change.

Continued

ADLER Silberlack (silver paint) 54814

Packaging

375 ml, 750 ml

Colour

Silver 54814 (ca. RAL 9006)

Storage

Dry and frost-protected
Please shut open containers well and upend them.

Safety information

Please pay attention to the safety information sheet!