

# ADLER Alkydharzturbo

**8054000210**

**Solvent-based curing agent for synthetic resin systems and oils for the trade**

## PRODUCT DESCRIPTION

### General

Solvent-based curing agent for transparent and opaque synthetic resin systems as well as oils for improving mechanical and chemical resistance and drying in unfavourable climatic drying conditions (temperature, humidity) and on timbers with high levels of substances in the wood.

### Application areas




- Curing components for solvent-based synthetic resin paints (such as ADLER Express Maschinenlack, ADLER Samtalkyd, ADLER Brilliantalkyd, ADLER Ferro GSX).
- Curing components for ADLER Legno-Öl.
- Curing components for solvent-based ADLER Pullex products (such as Pullex Color, Pullex Renovier-Grund, Pullex Plus-Lasur, Pullex Top-Lasur, Pullex High-Tech, etc.).
- Please observe the respective technical data sheets of the products.

## PROCESSING

### Instructions for use


- Carefully mix in ADLER Alkydharzturbo 8054000210 immediately after adding it to the paint components.
- Mixed paints must be processed as specified in the corresponding technical data sheet.

### Mixing ratio



100 parts by weight of ADLER Pullex products or ADLER Legno Öl  
 5-10 parts by weight of ADLER Alkydharzturbo 805400210  
 100 parts by weight of all other approved products  
 5-10 parts by weight of ADLER Alkydharzturbo 805400210

### Pot Life



8 hrs

Mixed paints must be used within one working day.

---

**ORDERING INFORMATION**


---

**Size of trading unit** 250ml, 500ml, 1l

---

**FURTHER DETAILS**

---

**Durability / storage**

At least 6 months in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Always close the lid immediately after use to prevent the ingress of humidity into the container.

---

**Safety-related information**

Please pay attention to the associated safety data sheet. The current version can be accessed on the Internet at **[www.adler-lacke.com](http://www.adler-lacke.com)**.

The product is only suitable for industrial and commercial processing.

---