


ADLER Woodwax

30720



Product Description

Water-thinnable, low viscosity wax emulsion for use indoors. It has deep penetration, and is thus particularly waterproof. It barely changes the inherent colour of the wood. The wax-like silky gloss appears immediately after drying without brushing out the surface.

Areas of application

Wall and ceiling panel-work and panels

Application method

Smearing (acrylic brush) and spraying (compressed air)

Coating

2 – 3 times with ADLER Woodwax 30720 undiluted (sand smoothly between the coats using grinding fleece)

In the case of tongue-and-groove boards we basically recommend application of one coat prior to installation; if this is not possible, apply only a little Woodwax in the tongue-and-groove area in order to prevent agglutination.

After-treatment

The surface can be brushed out after application of the final coat using a horsehair brush after which the wax-like appearance gets accentuated.

Dilution (thinning)

Water; the product is ready for application or use.

Processing and object temperature

Not below + 10 °C
High atmospheric humidity and / or low temperatures delay the drying process.

Drying (Room temperature 20 °C)

Can be sanded or recoated after about 3 hours

Tools and Equipment

Clean them with water immediately after use. Dry spraying devices well when finished in order to prevent rusting.
Removed dried up wax residue using ADLER Abbeizer Rote Krähe 95125.

Yield (per application)

10 - 15 m²/l

Container sizes

375 ml, 750 ml and 3 l

Storage

Store it in a cool place that is frost-free

Storage stability

3 years in the original sealed containers.

11-10 (supersedes 08-08) ZKL 7001

ADLER-Werk Lackfabrik, A-6130 Schwaz,
Fon: 0043/5242/6922-190, Fax: 0043/5242/6922-309, Mail: info@adler-lacke.com

Our instructions for use are based on knowledge available currently and shall guide the purchaser / user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The purchaser / user decides about the acceptance and use of the delivered product at his / her own risk, which is why we recommend that a sample piece be prepared to check the acceptability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for the modification of the container sizes, colour shades and degrees of gloss available.

Continued

ADLER Woodwax 30720

Colour shades

Farblos (Colourless) 30720 can be tinted; further colour shades can be mixed by the colour mixing system ADLER Color or Color4you.

Safety-related information

Please take note of and follow the safety data sheet!
The customary safety precautions must be observed and followed even when processing low-pollutant products.